

SSSB200 series



Bearing No.		d		D		Bi		Be		Dimensions				G		Ds		Weight (KG)
		in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
SS-SB201-8	SS-CSB201-8	1/2		1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.1
SS-SB201	SS-CSB201		12	1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.1
SS-SB202-9	SS-CSB202-9	9/16		1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.1
SS-SB202-10	SS-CSB202-10	5/8		1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.1
SS-SB202	SS-CSB202		15	1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.1
SS-SB203-11	SS-CSB203-11	11/16		1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.09
SS-SB203	SS-CSB203		17	1.5748	40	0.8661	22	0.4724	12	0.236	6	0.63	16	0.1969	5	1/4-28	M5P0.75	0.09
SS-SB204-12	SS-CSB204-12	3/4		1.85	47	0.9843	25	0.5512	14	0.276	7	0.709	18	0.1969	5	1/4-28	M6P0.75	0.14
SS-SB204	SS-CSB204		20	1.85	47	0.9843	25	0.5512	14	0.276	7	0.709	18	0.1969	5	1/4-28	M6P0.75	0.13
SS-SB205-14	SS-CSB205-14	7/8		2.0472	52	1.063	27	0.5906	15	0.295	7.5	0.768	19.5	0.1969	5	1/4-28	M6P0.75	0.18
SS-SB205-15	SS-CSB205-15	15/16		2.0472	52	1.063	27	0.5906	15	0.295	7.5	0.768	19.5	0.1969	5	1/4-28	M6P0.75	0.17
SS-SB205-16	SS-CSB205-16	1		2.0472	52	1.063	27	0.5906	15	0.295	7.5	0.768	19.5	0.1969	5	1/4-28	M6P0.75	0.16
SS-SB205	SS-CSB205		25	2.0472	52	1.063	27	0.5906	15	0.295	7.5	0.768	19.5	0.1969	5	1/4-28	M6P0.75	0.16
SS-SB206-17	SS-CSB206-17	1 1/16		2.4409	62	1.1811	30	0.6299	16	0.315	8	0.8661	22	0.1969	5	1/4-28	M6P0.75	0.28
SS-SB206-18	SS-CSB206-18	1 1/8		2.4409	62	1.1811	30	0.6299	16	0.315	8	0.8661	22	0.1969	5	1/4-28	M6P0.75	0.26
SS-SB206-19	SS-CSB206-19	1 3/16		2.4409	62	1.1811	30	0.6299	16	0.315	8	0.8661	22	0.1969	5	1/4-28	M6P0.75	0.25
SS-SB206	SS-CSB206		30	2.4409	62	1.1811	30	0.6299	16	0.315	8	0.8661	22	0.1969	5	1/4-28	M6P0.75	0.25
SS-SB207-20	SS-CSB207-20	1 1/4		2.8346	72	1.2598	32	0.6693	17	0.3346	8.5	0.9252	23.5	0.2362	6	5/16-24	M8P1.0	0.43
SS-SB207-21	SS-CSB207-21	1 5/16		2.8346	72	1.2598	32	0.6693	17	0.3346	8.5	0.9252	23.5	0.2362	6	5/16-24	M8P1.0	0.41
SS-SB207-22	SS-CSB207-22	1 3/8		2.8346	72	1.2598	32	0.6693	17	0.3346	8.5	0.9252	23.5	0.2362	6	5/16-24	M8P1.0	0.38
SS-SB207-23	SS-CSB207-23	1 7/16		2.8346	72	1.2598	32	0.6693	17	0.3346	8.5	0.9252	23.5	0.2362	6	5/16-24	M8P1.0	0.37
SS-SB207	SS-CSB207		35	2.8346	72	1.2598	32	0.6693	17	0.3346	8.5	0.9252	23.5	0.2362	6	5/16-24	M8P1.0	0.38
SS-SB208-24	SS-CSB208-24	1 1/2		3.1496	80	1.3386	34	0.7087	18	0.3543	9	0.9843	25	0.315	8	5/16-24	M8P1.0	0.58
SS-SB208-25	SS-CSB208-25	1 9/16		3.1496	80	1.3386	34	0.7087	18	0.3543	9	0.9843	25	0.315	8	5/16-24	M8P1.0	0.6
SS-SB208	SS-CSB208		40	3.1496	80	1.3386	34	0.7087	18	0.3543	9	0.9843	25	0.315	8	5/16-24	M8P1.0	0.6
SS-SB209-26	SS-CSB209-26	1 5/8		3.3465	85	1.662	41.2	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.0	0.8
SS-SB209-27	SS-CSB209-27	1 11/16		3.3465	85	1.662	41.2	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.0	0.8
SS-SB209-28	SS-CSB209-28	1 3/4		3.3465	85	1.662	41.2	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.0	0.8
SS-SB209	SS-CSB209		45	3.3465	85	1.662	41.2	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.0	0.8
SS-SB210-29	SS-CSB210-29	1 13/16		3.5433	90	1.7126	43.5	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.25	0.8
SS-SB210-30	SS-CSB210-30	1 7/8		3.5433	90	1.7126	43.5	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.25	0.8
SS-SB210-31	SS-CSB210-31	1 15/16		3.5433	90	1.7126	43.5	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.25	0.8
SS-SB210-32	SS-CSB210-32	2		3.5433	90	1.7126	43.5	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.25	0.8
SS-SB210	SS-CSB210		50	3.5433	90	1.7126	43.5	0.7874	20	0.4291	10.9	1.2834	32.6	0.3937	10	3/8-24	M10P1.25	0.8

SSSB200 series

SS-SB211-32	SS-CSB211-32	2		3.937	100	1.7835	43.5	0.8268	21	0.4646	11.8	33.5	33.5	0.3937	10	3/8-24	M10P125	1.1
SS-SB211-33	SS-CSB211-33	$\frac{2}{1/16}$		3.937	100	1.7835	43.5	0.8268	21	0.4646	11.8	33.5	33.5	0.3937	10	3/8-24	M10P125	1.1
SS-SB211-34	SS-CSB211-34	2 1/8		3.937	100	1.7835	43.5	0.8268	21	0.4646	11.8	33.5	33.5	0.3937	10	3/8-24	M10P125	1.1
SS-SB211-35	SS-CSB211-35	$\frac{2}{3/16}$		3.937	100	1.7835	43.5	0.8268	21	0.4646	11.8	33.5	33.5	0.3937	10	3/8-24	M10P125	1.1
SS-SB211	SS-CSB211		55	3.937	100	1.7835	43.5	0.8268	21	0.4646	11.8	33.5	33.5	0.3937	10	3/8-24	M10P125	1.1
SS-SB212-36	SS-CSB212-36	2 1/4		4.3307	110	2.1142	53.7	0.8661	22	0.5866	14.9	1.5276	38.8	0.3937	10	3/8-24	M10P125	1.3
SS-SB212-37	SS-CSB212-37	$\frac{2}{15/16}$		4.3307	110	2.1142	53.7	0.8661	22	0.5866	14.9	1.5276	38.8	0.3937	10	3/8-24	M10P125	1.3
SS-SB212-38	SS-CSB212-38	2 3/8		4.3307	110	2.1142	53.7	0.8661	22	0.5866	14.9	1.5276	38.8	0.3937	10	3/8-24	M10P125	1.3
SS-SB212-39	SS-CSB212-39	$\frac{2}{7/16}$		4.3307	110	2.1142	53.7	0.8661	22	0.5866	14.9	1.5276	38.8	0.3937	10	3/8-24	M10P125	1.3
SS-SB212	SS-CSB212		60	4.3307	110	2.1142	53.7	0.8661	22	0.5866	14.9	1.5276	38.8	0.3937	10	3/8-24	M10P125	1.3